



接线方式:

P1	P2	P1	P2
1	1	10	10
2	2	11	11
3	3	12	12
4	4	13	13
5	5	14	14
6	6	15	15
7	7	open	16
8	8		
9	9		

Testing requirements:

1. 100% OPEN SHORT & MISS WIRE TEST
2. MINI INSULATION RESISTANCE: MINI DC300V 5M Ohm
3. MAX. CONDUCTOR RESISTANCE: 3 Ohm

产品规格图

品名	15P串口线(300mm)	① Cable : UL2651 28AWG 16P Flat with Red line L=300mm	1PCS
颜色	<input checked="" type="checkbox"/> 灰 <input type="checkbox"/> 红 <input type="checkbox"/> 其它	② Connector : DB15P母头 (蓝胶芯)	1PCS
分发	<input checked="" type="checkbox"/> 品管 <input checked="" type="checkbox"/> 业务	③ Plastic insert : 15P Black DKN	1PCS
部门	<input checked="" type="checkbox"/> 工程 <input checked="" type="checkbox"/> 制造	④ Bracket : DB15P Metal	1PCS
		⑤ Nuts : Hex Nut	2PCS
		⑥ FC-16P	1PCS

	DRAWING NO :		07129	
	PAWT NO :			
FILE NO	REV : A/O	UNIT : MM	PAGE : 1/1	
APPROVE	CHECO BY	DRAWING BY	DATE :	