



NOTES:

1. MATERIALS

1.1 CABLE: [7/0.12BCX1P+7/0.20BCX2C+AM+7/0.12BC+B(16/3/0.12ALM)+BLACK PVC JACKET.

OD=∅4.5±0.15MM.

CABLE MARKING:USB 2.0 CABLE FULLY RATED 30V 80°C

1.2 CONNECTOR: P1: USB A TYPE MALE: SOLDER TYPE, BLACK PBT INSULATION, GOLD FLASH CONTACTS, GOLD PLATED SHELL.

1.3 P2: USB B TYPE MALE: SOLDER TYPE, BLACK PBT INSULATION, GOLD FLASH CONTACTS, GOLD PLATED SHELL.

1.4 ALL HOOD: MOLDED BLACK PVC.

2. 100% OPEN AND SHORT TEST.

3. PACKING: 1PCS/PE BAG.

4. ALL MATERIAL BE RoHS COMPLIANT.

PIN OUT

P1 ——— P2

1 ——— 1 RED

2 ——— 2 WHITE

3 ——— 3 GREEN

4 ——— 4 BLACK

SHELL ——— SHELL (BRAID+DRAIN)

——— > PAIR

LENGTH TOLERANCE:		SCALE:		CUS. NAME:		ENG:	
X. ± 0.5		FREE					
.X ± 0.2		UNIT:		PRODUCT NO:		CUSTOMER NO:	
.XX ± 0.1		mm				PCC70523	
ANGLE TOLERANCE:		VERSION:		DRAWING NO:		PRODUCT DESCRIPTION:	
X° ± 3°		00		0757		USB2.0 AM/BM	
.X° ± 1°		PAGE:		1/1		APPROVED:	
NEW ISSUE		2013-06-26					
MODIFY DESCRIPTION		DATE					