



CABLE MARKING:

HI-SPEED USB Revision 2.0 SHIELDED 28AWG/1PR+24AWG/2C
 E300060 允 AWM 2725 80°C 30V VW-1
 CSA 204790 AWM I/II A/B 80°C 30V FT1 MSL

9509-17			
P1		P2	
1	—————	1	RED 24#
2	———○———	2	WHITE
3	———○———	3	GREEN
4	—————	4	BLACK 24#
SHIELD	———○———	SHIELD	

* NOTE: All relevant materials are complied with RoHS directive.

3	MOLDED PVC BEIGE	H1BF01-0304B01		M304
2	USB 2.0 CABLE, UL 2725 STYLE 1 TWISTED PAIR 28AWG AND 2C 24AWG, AMA BRAID, OD 4.5mm, JACKET BEIGE, DRAWING No. EUAB2801P2402C-422	H5KT03-0304B01	L-20mm	M304
1	USB A MALE, GOLD FLASH ON CONTACTS, WHITE INSULATOR, CRIMP TWO PIECES TYPE	A1HA22-0454	2set	M454
No.	DESCRIPTION	Q'TY		Supplier

APPROVED		PCCABLES.COM INC.	Cable Length Unless Other Spec. Tolerances: 0 ~200mm ±10mm 201~1000mm ±20mm 1001 ~1500mm ±25mm 1501~2100mm ±30mm 2100mm↑ ±40mm
CHECKED	HU		
DRAWING	XIAO		
DATE	28/NOV/19		
ITEM NO.		UNIT:mm	

CHECKED