



SECTION A-A

PIN OUTS	PIN
----------	-----

5P HOUSING WIRE COLOR	5P HOUSING WIRE COLOR	5P HOUSING WIRE COLOR
1 RED	1 RED	1 RED
2 WHITE	2 WHITE	2 WHITE
3 GREEN	3 GREEN	3 GREEN
4 BLACK	4 BLACK	4 BLACK
5 DRAIN	5 DRAIN	5 DRAIN

NOTES:

- CABLE: {[28AWG(7/0.127)?1P+24AWG(7/0.203)?2C+AL/MY +DW(7/0.127)+85%BD(16/5/0.12)]*2F}TIN
- WIRE: A&B: 1P: FO-SKIN OD=ø0.80±0.05mm COLOR: WHITE&GREEN
2C: SR-PVC OD=ø1.10±0.05MM COLOR: RED&BLACK
- JACKET: 80°C PVC OD=ø(4.8*4.8)± 0.15mm
- COLOR: 3B70BP110CLEAR(transparent)
- FINISHED PRODUCTS LENGTH:
- 1.PCC344-1200 : L=35"±20mm
- 2.PCC344-1201 : L=16"±20mm

THIS PRODUCT MEETS ROHS REQUIREMENTS

TEST CONDITION: LOW-PRESSURE	15V
INSULATION: UPON 1M ohm	ELECTRIC CONDUCTION: INSIDE 1.5kohm
3 5P HOUSING	#H2205 BLACK
2 #33033BS-2A Terminal	
1 CABLE: 28AWG*1P+24AWG*2C	TRANSPARENT
ITEM NO	

PRODUCT	5P HOUSING(*2) TO 5P HOUSING	DRAWN		THREE ANGLE PROJECTION
CUS NO	PCC344-12XX	CHECKED		
DR,NO		APPROVERD		